

# Septone Brake Dust Cleaner

ITW AAMTech

Chemwatch Hazard Alert Code: 3

Chemwatch: 5158-79

Issue Date: 30/01/2015

Version No: 3.1.1.1

Print Date: 04/02/2015

Material Safety Data Sheet according to NOHSC and ADG requirements

Initial Date: **Not Available**

S.Local.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

<b>Product name</b>	Septone Brake Dust Cleaner
<b>Chemical Name</b>	Not Applicable
<b>Synonyms</b>	Product Code: ADBC20
<b>Proper shipping name</b>	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. (see 3.2.5 for relevant [AUST.] entries) (contains naphtha petroleum, light aliphatic solvent)
<b>Chemical formula</b>	Not Applicable
<b>Other means of identification</b>	Not Available
<b>CAS number</b>	Not Applicable

### Relevant identified uses of the substance or mixture and uses advised against

<b>Relevant identified uses</b>	Fast drying solvent based brake dust cleaner.
---------------------------------	---

### Details of the manufacturer/importer

<b>Registered company name</b>	ITW AAMTech
<b>Address</b>	100 Hassall Street 2164 NSW Australia
<b>Telephone</b>	1800 177 989
<b>Fax</b>	1800 308 556
<b>Website</b>	www.aamtech.com.au
<b>Email</b>	info@aamtech.com.au

### Emergency telephone number

<b>Association / Organisation</b>	Not Available
<b>Emergency telephone numbers</b>	1800 039 008
<b>Other emergency telephone numbers</b>	+61 3 9573 3112

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

<b>Poisons Schedule</b>	S5
<b>Risk Phrases [1]</b>	<b>R51/53</b> Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	<b>R67</b> Vapours may cause drowsiness and dizziness.
	<b>R65</b> HARMFUL-May cause lung damage if swallowed.
	<b>R62(3)</b> Possible risk of impaired fertility.
	<b>R48/20</b> Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Continued...

## Septone Brake Dust Cleaner

	<b>R38</b>	Irritating to skin.
	<b>R11</b>	Highly flammable.
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	
<b>GHS Classification</b> <sup>[1]</sup>	Flammable Liquid Category 2, Skin Corrosion/Irritation Category 2, Reproductive Toxicity Category 2, STOT - SE (Narcosis) Category 3, STOT - RE Category 2, Aspiration Hazard Category 1, Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2	
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	

### Label elements

<b>GHS label elements</b>	
---------------------------	---

<b>SIGNAL WORD</b>	<b>DANGER</b>
--------------------	---------------

### Hazard statement(s)

<b>H225</b>	Highly flammable liquid and vapour
<b>H315</b>	Causes skin irritation
<b>H361</b>	Suspected of damaging fertility or the unborn child
<b>H336</b>	May cause drowsiness or dizziness
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure
<b>H304</b>	May be fatal if swallowed and enters airways
<b>H401</b>	Toxic to aquatic life
<b>H411</b>	Toxic to aquatic life with long lasting effects

### Precautionary statement(s) Prevention

<b>P201</b>	Obtain special instructions before use.
<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P260</b>	Do not breathe dust/fume/gas/mist/vapours/spray.
<b>P271</b>	Use only outdoors or in a well-ventilated area.

### Precautionary statement(s) Response

<b>P301+P310</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
<b>P308+P313</b>	IF exposed or concerned: Get medical advice/attention.
<b>P331</b>	Do NOT induce vomiting.
<b>P370+P378_1</b>	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.

### Precautionary statement(s) Storage

<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.
<b>P405</b>	Store locked up.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.

### Precautionary statement(s) Disposal

<b>P501</b>	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
-------------	--

### Label elements



Relevant risk statements are found in section 2

<b>Indication(s) of danger</b>	F, N, Xn
--------------------------------	----------

## Septone Brake Dust Cleaner

### SAFETY ADVICE

<b>S01</b>	Keep locked up.
<b>S07</b>	Keep container tightly closed.
<b>S09</b>	Keep container in a well ventilated place.
<b>S13</b>	Keep away from food, drink and animal feeding stuffs.
<b>S16</b>	Keep away from sources of ignition. No smoking.
<b>S20</b>	When using do not eat or drink.
<b>S23</b>	Do not breathe gas/fumes/vapour/spray.
<b>S28</b>	After contact with skin, wash immediately with plenty of water
<b>S29</b>	Do not empty into drains.
<b>S33</b>	Take precautionary measures against static discharges.
<b>S35</b>	This material and its container must be disposed of in a safe way.
<b>S36</b>	Wear suitable protective clothing.
<b>S37</b>	Wear suitable gloves.
<b>S38</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>S40</b>	To clean the floor and all objects contaminated by this material, use water and detergent.
<b>S41</b>	In case of fire and/or explosion, DO NOT BREATHE FUMES.
<b>S43</b>	In case of fire use...
<b>S45</b>	In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).
<b>S46</b>	If swallowed, seek medical advice immediately and show this container or label.
<b>S51</b>	Use only in well ventilated areas.
<b>S53</b>	Avoid exposure - obtain special instructions before use.
<b>S56</b>	Dispose of this material and its container at hazardous or special waste collection point.
<b>S57</b>	Use appropriate container to avoid environmental contamination.
<b>S61</b>	Avoid release to the environment. Refer to special instructions/Safety data sheets.
<b>S64</b>	If swallowed, rinse mouth with water (only if the person is conscious).

### Other hazards

	Inhalation, skin contact and/or ingestion may produce health damage*.
	May produce discomfort of the eyes and respiratory tract*.

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
64742-89-8.	>60	<a href="#">naphtha petroleum, light aliphatic solvent</a>
110-54-3	10-30	<a href="#">n-hexane</a>
67-63-0	<20	<a href="#">isopropanol</a>
100-41-4	<10	<a href="#">ethylbenzene</a>
		contains <0.1% w/w benzene

## SECTION 4 FIRST AID MEASURES

### Description of first aid measures

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
--------------------	---

Continued...

## Septone Brake Dust Cleaner

<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<p>If poisoning occurs, contact a doctor or Poisons Information Centre.</p> <ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- ▶ Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- ▶ Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- ▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- ▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- ▶ Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

	<ul style="list-style-type: none"> <li>▶ Foam.</li> <li>▶ Dry chemical powder.</li> <li>▶ BCF (where regulations permit).</li> <li>▶ Carbon dioxide.</li> </ul>
--	---

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	Avoid contamination with strong oxidising agents as ignition may result
-----------------------------	---

### Advice for firefighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> </ul>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> </ul>

- ▶ May be violently or explosively reactive.
- ▶ Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>Avoid generating and breathing mist and vapour               <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> </ul> </li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> </ul>

### Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul>
<b>Storage incompatibility</b>	Avoid storage with oxidisers

#### PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	n-hexane	Hexane (n-Hexane)	72 mg/m <sup>3</sup> / 20 ppm	Not Available	Not Available	Not Available
Australia Exposure Standards	isopropanol	Isopropyl alcohol	983 mg/m <sup>3</sup> / 400 ppm	1230 mg/m <sup>3</sup> / 500 ppm	Not Available	Not Available
Australia Exposure Standards	ethylbenzene	Ethyl benzene	434 mg/m <sup>3</sup> / 100 ppm	543 mg/m <sup>3</sup> / 125 ppm	Not Available	Not Available

#### EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
naphtha petroleum, light aliphatic solvent	Rubber solvent; (Naphtha (petroleum) light aliphatic)	264 ppm	1700 ppm	10000 ppm
n-hexane	Hexane	300 ppm	Not Available	Not Available
isopropanol	Isopropyl alcohol	400 ppm	400 ppm	12000 ppm
ethylbenzene	Ethyl benzene	Not Available	Not Available	Not Available


Ingredient	Original IDLH	Revised IDLH
naphtha petroleum, light aliphatic solvent	Not Available	Not Available
n-hexane	5,000 ppm	1,100 [LEL] ppm
isopropanol	12,000 ppm	2,000 [LEL] ppm
ethylbenzene	2,000 ppm	800 [LEL] ppm

### Exposure controls

<b>Appropriate engineering controls</b>	<b>CARE:</b> Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear
---	--

Continued...

## Septone Brake Dust Cleaner

	Use in a well-ventilated area or Local exhaust ventilation may be required for safe working, i.e. to keep exposures below required standards, otherwise PPE is required. In confined spaces where there is inadequate ventilation, wear full-face air supplied breathing apparatus
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields; or as required,</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Barrier cream with polyethylene gloves</li> <li>▶ PVC gloves</li> <li>▶ Protective footwear</li> <li>▶ <b>DO NOT use this product to clean the skin</b></li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Eyewash unit.</li> </ul>
<b>Thermal hazards</b>	Not Available

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Septone Brake Dust Cleaner

Material	CPI
BUTYL	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE/EVAL/PE	C
PVA	C
PVC	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/CHLOROBUTYL	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	AX-AUS / Class 1 P2	-	AX-PAPR-AUS / Class 1 P2
up to 25 x ES	Air-line*	AX-2 P2	AX-PAPR-2 P2
up to 50 x ES	-	AX-3 P2	-
50+ x ES	-	Air-line**	-

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	Clear water white mobile highly flammable liquid with hydrocarbon solvent odour; floats on water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.715
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	350
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not available.	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	50-135	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	-30 (Abel - IP170)	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	6.9 BuAC = 1	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	7.5	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	1.0	<b>Volatile Component (%vol)</b>	100
<b>Vapour pressure (kPa)</b>	34.5 @ 20C	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Immiscible	<b>pH as a solution(1%)</b>	Not Applicable
<b>Vapour density (Air = 1)</b>	>1	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

<b>Inhaled</b>	Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.
<b>Ingestion</b>	Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis. Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.
<b>Skin Contact</b>	This material can cause inflammation of the skin on contact in some persons. Toxic effects may result from skin absorption The material may accentuate any pre-existing skin condition Open cuts, abraded or irritated skin should not be exposed to this material

### Septone Brake Dust Cleaner

<b>Eye</b>	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.	
<b>Chronic</b>	Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS] Chronic inhalation or skin exposure to n-hexane may cause damage to nerve ends in extremities, e.g. finger, toes with loss of sensation.	
<b>Septone Brake Dust Cleaner</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>naphtha petroleum, light aliphatic solvent</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>n-hexane</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation (rat) LD50: 48000 ppm/4h	Eye(rabbit): 10 mg - mild
	Oral (rat) LD50: 28710 mg/kg	
	Not Available	Not Available
<b>isopropanol</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 12800 mg/kg	Eye (rabbit): 10 mg - moderate
	Inhalation (Mouse) LC50: 53000 mg/m <sup>3</sup> /4h	Eye (rabbit): 100 mg - SEVERE
	Inhalation (Rat) LC50: 72600 mg/m <sup>3</sup> /4h	Eye (rabbit): 100mg/24hr-moderate
	Intraperitoneal (Guinea pig) LD50: 2560 mg/kg	Skin (rabbit): 500 mg - mild
	Intraperitoneal (Mouse) LD50: 4477 mg/kg	
	Intraperitoneal (Rabbit) LD50: 667 mg/kg	
	Intraperitoneal (Rat) LD50: 2735 mg/kg	
	Intravenous (Mouse) LD50: 1509 mg/kg	
	Intravenous (Rabbit) LD50: 1184 mg/kg	
	Intravenous (Rat) LD50: 1088 mg/kg	
	Oral (Mouse) LD50: 3600 mg/kg	
	Oral (Rabbit) LD50: 6410 mg/kg	
	Oral (Rat) LD50: 5000 mg/kg	
	Oral (rat) LD50: 5045 mg/kg	
	Not Available	Not Available
<b>ethylbenzene</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 17800 mg/kg	Eye (rabbit): 500 mg - SEVERE
	Intraperitoneal (mouse) LD50: 2642 mg/kg	Skin (rabbit): 15 mg/24h mild
	Oral (rat) LD50: 3500 mg/kg	
	Not Available	Not Available

Not available. Refer to individual constituents.

Continued...



## Septone Brake Dust Cleaner

<b>NAPHTHA PETROLEUM, LIGHT ALIPHATIC SOLVENT</b>	<p><b>for petroleum:</b> This product contains benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic.</p> <p>This product contains toluene. There are indications from animal studies that prolonged exposure to high concentrations of toluene may lead to hearing loss.</p> <p>This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents</p> <p><b>Carcinogenicity:</b> Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.</p>
<b>N-HEXANE</b>	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
<b>ISOPROPANOL</b>	Isopropanol is irritating to the eyes, nose and throat but generally not to the skin. Prolonged high dose exposure may also produce depression of the central nervous system and drowsiness. Few have reported skin irritation. It can be absorbed from the skin or when inhaled.
<b>ETHYLBENZENE</b>	<p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>Ethylbenzene is readily absorbed when inhaled, swallowed or in contact with the skin.</p> <p>Liver changes, uterual tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded.</p>

<b>Acute Toxicity</b>	☹	<b>Carcinogenicity</b>	☹
<b>Skin Irritation/Corrosion</b>	✔	<b>Reproductivity</b>	✔
<b>Serious Eye Damage/Irritation</b>	☹	<b>STOT - Single Exposure</b>	✔
<b>Respiratory or Skin sensitisation</b>	☹	<b>STOT - Repeated Exposure</b>	✔
<b>Mutagenicity</b>	☹	<b>Aspiration Hazard</b>	✔

**Legend:**   ✔ – Data required to make classification available  
                   ✘ – Data available but does not fill the criteria for classification  
                   ☹ – Data Not Available to make classification

### CMR STATUS

Not Applicable

### SECTION 12 ECOLOGICAL INFORMATION

#### Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DO NOT discharge into sewer or waterways.**

[The volatile components of this product are readily biodegradable under aerobic conditions. They will partition largely to the atmosphere but some will partition to soil and sediment where lowered bioavailability would reduce uptake by organisms. Research also indicates that the volatile components have a moderate potential for bioaccumulation; however bioconcentration would be expected to be low. They are expected to exhibit a moderate toxicity to aquatic organisms.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-hexane	LOW	LOW
isopropanol	LOW (Half-life = 14 days)	LOW (Half-life = 3 days)
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)

#### Bioaccumulative potential

Ingredient	Bioaccumulation
n-hexane	MEDIUM (LogKOW = 3.9)
isopropanol	LOW (LogKOW = 0.05)
ethylbenzene	LOW (BCF = 79.43)

#### Mobility in soil

Continued...

Septone Brake Dust Cleaner

Ingredient	Mobility
n-hexane	LOW (KOC = 149)
isopropanol	HIGH (KOC = 1.06)
ethylbenzene	LOW (KOC = 517.8)



SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> <li>▶ Consult manufacturer for recycling options and recycle where possible .</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul>
------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	
HAZCHEM	3YE

Land transport (ADG)

UN number	1268
Packing group	II
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. (see 3.2.5 for relevant [AUST.] entries) (contains naphtha petroleum, light aliphatic solvent)
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 3 Subrisk : Not Applicable
Special precautions for user	Special provisions : 363 Limited quantity : 1 L

Air transport (ICAO-IATA / DGR)

UN number	1268
Packing group	II
UN proper shipping name	Petroleum distillates, n.o.s.; Petroleum products, n.o.s. (contains naphtha petroleum, light aliphatic solvent)
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 3 ICAO / IATA Subrisk : Not Applicable ERG Code : 3H
Special precautions for user	Special provisions : A3 Cargo Only Packing Instructions : 364 Cargo Only Maximum Qty / Pack : 60 L Passenger and Cargo Packing Instructions : 353 Passenger and Cargo Maximum Qty / Pack : 5 L Passenger and Cargo Limited Quantity Packing Instructions : Y341 Passenger and Cargo Limited Maximum Qty / Pack : 1 L

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	1268	
<b>Packing group</b>	II	
<b>UN proper shipping name</b>	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. (contains naphtha petroleum, light aliphatic solvent)	
<b>Environmental hazard</b>	No relevant data	
<b>Transport hazard class(es)</b>	IMDG Class	3
	IMDG Subrisk	Not Applicable
<b>Special precautions for user</b>	EMS Number	F-E , S-E
	Special provisions	363
	Limited Quantities	1 L

**Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code**

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	n-hexane	X; Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	ethylbenzene	Y

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture**

<b>naphtha petroleum, light aliphatic solvent(64742-89-8.) is found on the following regulatory lists</b>	"Australia Inventory of Chemical Substances (AICS)", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Hazardous Substances Information System - Consolidated Lists"
<b>n-hexane(110-54-3) is found on the following regulatory lists</b>	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
<b>isopropanol(67-63-0) is found on the following regulatory lists</b>	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"
<b>ethylbenzene(100-41-4) is found on the following regulatory lists</b>	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"

**SECTION 16 OTHER INFORMATION****Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.